

## **P/N NAS6303L2**

### **Description**

Fastener Length: 29/64", Thread: 10-32, Thread Length: 11/32"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS6303L2

Minimum Qty (MOQ): 10 EA

NSN: 5306-01-083-1599

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS6303L2 Specifications**

Thread Class: 3	За
Thread Direction:	Right-hand
Thread Length: 0	0.298 Inches Minimum And 0.348 Inches Maximum
Fastener Length: 0	0.433 Inches Minimum And 0.463 Inches Maximum
Head Style:	Dished Hexagon
Head Height: 0	0.110 Inches Minimum And 0.125 Inches Maximum
Width Between Flats: 0	0.367 Inches Minimum And 0.376 Inches Maximum
Locking Feature:	Pellet Threads Or Patch Threads Or Strip Threads
Grip Diameter: 0	0.1885 Inches Minimum And 0.1895 Inches Maximum
Nominal Thread Diameter: 0	0.190 Inches
Grip Length: 0	0.115 Inches Minimum And 0.135 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength: 1	160000 Pounds Per Square Inch
Surface Finish: 3	32.0 Microinches Bearing Surface Of Head
Surface Finish: 3	32.0 Microinches Grip
Surface Finish: 3	32.0 Microinches Threads
Material:	ron Alloy 660 Fastener
Material:	Plastic Polyamide Locking Feature
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Fastener Or Ams 5737 Assn Std Single Material Response Fastener
Surface Treatment:	Passivate Fastener
Surface Treatment Document And Classification:	Nas 4003 Assn Std Single Treatment Response Fastener
Thread Series Designator:	Unjf

## **How to Order**

Order this bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/shear+bolts/NAS6303L2">https://military-fasteners.com/bolts/shear+bolts/NAS6303L2</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.