

P/N NAS6303L2

Description

Fastener Length: 29/64", Thread: 10-32, Thread Length: 11/32"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS6303L2

Minimum Qty (MOQ): 10 EA

NSN: 5306-01-083-1599

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS6303L2 Specifications

Thread Class: 3a	a e e e e e e e e e e e e e e e e e e e
Thread Direction:	light-hand
Thread Length: 0.	.298 Inches Minimum And 0.348 Inches Maximum
Fastener Length: 0.	.433 Inches Minimum And 0.463 Inches Maximum
Head Style: Di	Dished Hexagon
Head Height: 0.	.110 Inches Minimum And 0.125 Inches Maximum
Width Between Flats: 0.	.367 Inches Minimum And 0.376 Inches Maximum
Locking Feature: Pe	ellet Threads Or Patch Threads Or Strip Threads
Grip Diameter: 0.	.1885 Inches Minimum And 0.1895 Inches Maximum
Nominal Thread Diameter: 0.	.190 Inches
Grip Length: 0.	.115 Inches Minimum And 0.135 Inches Maximum
Thread Quantity Per Inch: 32	2
Minimum Tensile Strength: 16	60000 Pounds Per Square Inch
Surface Finish: 32	2.0 Microinches Bearing Surface Of Head
Surface Finish: 32	2.0 Microinches Grip
Surface Finish: 32	2.0 Microinches Threads
Material: Iro	on Alloy 660 Fastener
Material: Pl	lastic Polyamide Locking Feature
Material Document And Classification: Ar	ıms 5731 Assn Std Single Material Response Fastener Or Ams 5737 Assn Std Single Material Response Fastener
Surface Treatment: Pa	assivate Fastener
Surface Treatment Document And Classification: Na	las 4003 Assn Std Single Treatment Response Fastener
Thread Series Designator:	lnjf

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/NAS6303L2 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.