



Military-Fasteners.com

P/N NAS6303U11D

Description

Fastener Length: 0-63/64", Thread: 10-32, Thread Length: 11/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS6303U11D |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5306-00-526-0530 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N NAS6303U11D Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.298 Inches Minimum And 0.348 Inches Maximum |
| Fastener Length: | 0.996 Inches Minimum And 1.026 Inches Maximum |
| Head Style: | Dished Hexagon |
| Head Height: | 0.110 Inches Minimum And 0.125 Inches Maximum |
| Width Between Flats: | 0.367 Inches Minimum And 0.376 Inches Maximum |
| Grip Diameter: | 0.1890 Inches Minimum And 0.1895 Inches Maximum |
| Shank Unthreaded Hole Diameter: | 0.070 Inches Minimum First Hole And 0.080 Inches Maximum First Hole |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 0.678 Inches Minimum And 0.698 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Distance From Head Largest Bearing Surface To Shank Hole Center: | 0.822 Inches Minimum First Hole And 0.872 Inches Maximum First Hole |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams5731 Assn Std Single Material Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas6303 Professional/Industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6303U11D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.