

Description

Fastener Length: 1-21/64", Thread: 10-32, Thread Length: 5/16

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6303U16D
Minimum Qty (MOQ):	5
NSN:	5306-01-321-8045
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS6303U16D Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.323 Inches Nominal
Fastener Length:	1.308 Inches Minimum And 1.338 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.110 Inches Minimum And 0.125 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Grip Diameter:	0.1890 Inches Minimum And 0.1895 Inches Maximum
Shank Unthreaded Hole Diameter:	0.070 Inches Minimum First Hole And 0.080 Inches Maximum First Hole
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.990 Inches Minimum And 1.010 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Distance From Head Largest Bearing Surface To Shank Hole Center:	1.134 Inches Minimum First Hole And 1.184 Inches Maximum First Hole
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80203-nas6303 Professional/Industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6303U16D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.