

**Description**

Fastener Length: 1-3/8", Thread: 10-32, Thread Length: 5/16",

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS6303U17
Minimum Qty (MOQ):	10
NSN:	5306-01-537-1035
Schedule B:	7318.15.8085
ECCN:	EAR99



## P/N NAS6303U17 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.323 Inches Nominal
<b>Fastener Length:</b>	1.385 Inches Nominal
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.110 Inches Minimum And 0.125 Inches Maximum
<b>Width Between Flats:</b>	0.367 Inches Minimum And 0.376 Inches Maximum
<b>Grip Diameter:</b>	0.1890 Inches Minimum And 0.1895 Inches Maximum
<b>Shank Unthreaded Hole Diameter:</b>	0.070 Inches Minimum First Hole And 0.080 Inches Maximum First Hole
<b>End Item Identification:</b>	Rq-4a
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Grip Length:</b>	1.062 Inches Nominal
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b>	1.196 Inches Minimum First Hole And 1.246 Inches Maximum First Hole
<b>Part Name Assigned By Controlling Agency:</b>	Bolt,shear
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6303U17> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.