

Description

length: 0.448", grip: 0.125", thread: 10-32, hex head, short thread, unplated corrosion resistant steel, NAS6303 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS6303U2 |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5306-00-295-8773 |
| Schedule B: | 7318.15.2095 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N NAS6303U2 Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.298 Inches Minimum And 0.348 Inches Maximum |
| Fastener Length: | 0.433 Inches Minimum And 0.463 Inches Maximum |
| Head Style: | Dished Hexagon |
| Head Height: | 0.110 Inches Minimum And 0.125 Inches Maximum |
| Width Between Flats: | 0.367 Inches Minimum And 0.376 Inches Maximum |
| Grip Diameter: | 0.1890 Inches Minimum And 0.1895 Inches Maximum |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 0.115 Inches Minimum And 0.135 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Surface Finish: | 32.0 Microinches Bearing Surface Of Head |
| Surface Finish: | 32.0 Microinches Grip |
| Surface Finish: | 32.0 Microinches Threads |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams 5731 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas6303 Professional/Industrial Association Standard |

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6303U2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.