

Description

Fastener Length: 1-41/64", Thread: 10-32, Thread Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS6303U21 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5306-01-544-8573 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |

NO IMAGE
AVAILABLE

P/N NAS6303U21 Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.323 Inches Nominal |
| Fastener Length: | 1.620 Inches Minimum And 1.650 Inches Maximum |
| Head Style: | Dished Hexagon |
| Head Height: | 0.110 Inches Minimum And 0.125 Inches Maximum |
| Width Between Flats: | 0.367 Inches Minimum And 0.376 Inches Maximum |
| Locking Feature: | Patch Threads |
| Grip Diameter: | 0.1890 Inches Minimum And 0.1895 Inches Maximum |
| End Item Identification: | Rq-4a |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 1.302 Inches Minimum And 1.322 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Material: | Plastic Polyamide Locking Feature |
| Material Document And Classification: | Ams5731 Assn Std Single Material Response Fastener Or Ams5737 Assn Std Single Material Response Fastener |
| Surface Treatment: | Passivate Fastener |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6303U21> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.