



Military-Fasteners.com

P/N NAS6303U33

## Description

Fastener Length: 2-25/64", Thread: 10-32, Thread Length: 11/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS6303U33                                |
| Minimum Qty (MOQ):      | 15 EA                                     |
| NSN:                    | 5306-01-463-4908                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N NAS6303U33 Specifications

|  |  |
|--|--|
| <b>Thread Class:</b>                         | 3a   |
| <b>Thread Direction:</b>                     | Right-hand   |
| <b>Thread Length:</b>                        | 0.298 Inches Minimum And 0.348 Inches Maximum  |
| <b>Fastener Length:</b>                      | 2.371 Inches Minimum And 2.401 Inches Maximum  |
| <b>Head Style:</b>                           | Dished Hexagon   |
| <b>Head Height:</b>                          | 0.110 Inches Minimum And 0.125 Inches Maximum  |
| <b>Width Between Flats:</b>                  | 0.367 Inches Minimum And 0.376 Inches Maximum  |
| <b>Grip Diameter:</b>                        | 0.1885 Inches Minimum And 0.1895 Inches Maximum  |
| <b>Nominal Thread Diameter:</b>              | 0.190 Inches   |
| <b>Grip Length:</b>                          | 2.053 Inches Minimum And 2.073 Inches Maximum  |
| <b>Thread Quantity Per Inch:</b>             | 32   |
| <b>Minimum Tensile Strength:</b>             | 160000 Pounds Per Square Inch  |
| <b>Surface Finish:</b>                       | 32.0 Microinches Bearing Surface Of Head   |
| <b>Surface Finish:</b>                       | 32.0 Microinches Threads   |
| <b>Material:</b>                             | Iron Alloy 660 Overall   |
| <b>Material Document And Classification:</b> | Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall |
| <b>Thread Series Designator:</b>             | Unjf   |
| <b>Specification/standard Data:</b>          | 80205-nas6303 Professional/industrial Association Standard   |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6303U33> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.