

**Description**

Fastener Length: 3-37/64", Thread: 10-32, Thread Length: 5/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                                           |
|-------------------------|-------------------------------------------|
| SKU / Model:            | NAS6303U52                                |
| Minimum Qty (MOQ):      | 1 EA                                      |
| NSN:                    | 5306-01-444-8416                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N NAS6303U52 Specifications

|                                     |                                                               |
|-------------------------------------|---------------------------------------------------------------|
| <b>Thread Class:</b>                | 3a                                                            |
| <b>Thread Direction:</b>            | Right-hand                                                    |
| <b>Thread Length:</b>               | 0.323 Inches Minimum                                          |
| <b>Fastener Length:</b>             | 3.558 Inches Minimum And 3.588 Inches Maximum                 |
| <b>Head Style:</b>                  | Dished Hexagon                                                |
| <b>Head Height:</b>                 | 0.110 Inches Minimum And 0.125 Inches Maximum                 |
| <b>Width Between Flats:</b>         | 0.367 Inches Minimum And 0.376 Inches Maximum                 |
| <b>Grip Diameter:</b>               | 0.1890 Inches Minimum And 0.1895 Inches Maximum               |
| <b>Nominal Thread Diameter:</b>     | 0.190 Inches                                                  |
| <b>Grip Length:</b>                 | 3.240 Inches Minimum And 3.260 Inches Maximum                 |
| <b>Thread Quantity Per Inch:</b>    | 32                                                            |
| <b>Minimum Tensile Strength:</b>    | 160000 Pounds Per Square Inch                                 |
| <b>Material:</b>                    | Iron Alloy 660 Overall                                        |
| <b>Surface Treatment:</b>           | Passivate Overall                                             |
| <b>Thread Series Designator:</b>    | Unjf                                                          |
| <b>Specification/standard Data:</b> | 80205-nas6303u52 Professional/Industrial Association Standard |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6303U52> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.