

P/N NAS6304-46D

Description

Fastener Length: 3-1/4", Thread: 1/4-28, Thread Length:

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NAS630446D
Minimum Qty (MOQ):	5
NSN:	5306-01-353-6111
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS6304-46D Specifications

3a
Right-hand
0.370 Inches Nominal
3.230 Inches Minimum And 3.260 Inches Maximum
Dished Hexagon
0.125 Inches Minimum And 0.140 Inches Maximum
0.429 Inches Minimum And 0.439 Inches Maximum
0.2485 Inches Minimum And 0.2495 Inches Maximum
0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole
0.250 Inches
2.865 Inches Minimum And 2.885 Inches Maximum
28
160000 Pounds Per Square Inch
3.050 Inches Minimum First Hole And 3.100 Inches Maximum First Hole
32.0 Microinches Bearing Surface Of Head32.0 Microinches Grip32.0 Microinches Threads
Iron Alloy 660 Overall
Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Cadmium Overall And Chromate Overall
Qq-p-416 Type 2,class 2 Fed Spec Single Treatment Response Overall
Unjf

How to Order

Order this shear bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/NAS6304-46D and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.