

Description

Fastener Length: 5/8", Hole Diameter: 5/64", Thread: 1/4-28, Thread Length: "

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS63045D
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-591-1378
Schedule B:	7318.15.2091
ECCN:	9A991



* See page 2 for technical characteristics

P/N NAS6304-5D Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.370 Inches Nominal
Fastener Length:	0.682 Inches Nominal
Head Style:	Hexagon
Head Height:	0.125 Inches Nominal
Width Between Flats:	0.429 Nominal Mils And 0.439 Nominal Centimeters
Hole Diameter:	0.081 Inches Nominal
Grip Diameter:	0.2485 Nominal Mils And 0.2495 Nominal Centimeters
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.312 Nominal Inches
Hole Quantity:	1
Hole Type:	Drilled
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hole Configuration Style:	Round
Material:	Iron Alloy 660 Fastener
Material:	Plastic Polyamide Locking Feature
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Fastener Or Ams 5732 Assn Std Single Material Response Fastener Or Ams 5737 Assn Std Single Material Response Fastener Or Ams 5853 Assn Std Single Material Response Fastener
Material Document And Classification:	Mil-dtl-18240 Mil Spec Single Material Response Locking Feature
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416, Type Ii, Class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6304-5D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.