



Military-Fasteners.com

P/N NAS6304P28H

Description

Fastener Length: 2-1/8", Thread: 1/4-28, Thread Length: "

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6304P28H
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-590-4559
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS6304P28H Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.370 Inches Nominal
Fastener Length:	2.105 Inches Minimum And 2.135 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Width Between Flats:	0.429 Inches Minimum And 0.439 Inches Maximum
Locking Feature:	Patch Threads
Grip Diameter:	0.249 Inches Minimum And 0.250 Inches Maximum
End Item Identification:	Warhead Section Harpoon Missile
Nominal Thread Diameter:	0.250 Inches
Grip Length:	1.740 Inches Minimum And 1.760 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Part Name Assigned By Controlling Agency:	Bolt Tension Hex Head Close Tolerance, A286 Cres Short Thread Reduced Major Thread Diameter Self-locking, 160 Ksi Ftu
Special Features:	Bolt With Drilled Head
Material:	Iron Alloy 660 Fastener
Material:	Plastic Polyamide Locking Feature
Surface Treatment:	Passivate Fastener
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6304P28H> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.