

Description

Fastener Length: 0.62", Hole Diameter: 1/32", Thread: 1/4-28, NAS6304 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS6304PU4H |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5306-01-580-5884 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |



P/N NAS6304PU4H Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.370 Inches Nominal |
| Fastener Length: | 0.620 Inches Nominal |
| Head Style: | Dished Hexagon |
| Head Height: | 0.125 Inches Minimum And 0.140 Inches Maximum |
| Width Between Flats: | 0.429 Inches Minimum And 0.439 Inches Maximum |
| Hole Diameter: | 0.046 Inches Nominal |
| Locking Feature: | Patch Threads |
| Grip Diameter: | 0.249 Inches Nominal |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 0.250 Inches Nominal |
| Hole Quantity: | 3 |
| Hole Type: | Drilled |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hole Configuration Style: | Hexagon Corners |
| Material: | Iron Alloy 660 Overall |
| Material: | Plastic Polyamide Locking Feature |
| Material Document And Classification: | Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Ams 2700, Method 1, Ty2 Or Ty8, Cl1 Assn Std Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6304PU4H> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.