

**Description**

Fastener Length: 0.62", Hole Diameter: 1/32", Thread: 1/4-28, NAS6304 series bolt

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                    |                  |
|--------------------|------------------|
| SKU / Model:       | NAS6304PU4H      |
| Minimum Qty (MOQ): | 5                |
| NSN:               | 5306-01-580-5884 |
| Schedule B:        | 7318.15.8085     |
| ECCN:              | EAR99            |



\* See page 2 for technical characteristics

## P/N NAS6304PU4H Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Thread Length:</b>                                 | 0.370 Inches Nominal   |
| <b>Fastener Length:</b>                               | 0.620 Inches Nominal   |
| <b>Head Style:</b>                                    | Dished Hexagon   |
| <b>Head Height:</b>                                   | 0.125 Inches Minimum And 0.140 Inches Maximum  |
| <b>Width Between Flats:</b>                           | 0.429 Inches Minimum And 0.439 Inches Maximum  |
| <b>Hole Diameter:</b>                                 | 0.046 Inches Nominal   |
| <b>Locking Feature:</b>                               | Patch Threads  |
| <b>Grip Diameter:</b>                                 | 0.249 Inches Nominal   |
| <b>Nominal Thread Diameter:</b>                       | 0.250 Inches   |
| <b>Grip Length:</b>                                   | 0.250 Inches Nominal   |
| <b>Hole Quantity:</b>                                 | 3  |
| <b>Hole Type:</b>                                     | Drilled  |
| <b>Thread Quantity Per Inch:</b>                      | 28   |
| <b>Minimum Tensile Strength:</b>                      | 160000 Pounds Per Square Inch  |
| <b>Hole Configuration Style:</b>                      | Hexagon Corners  |
| <b>Material:</b>                                      | Iron Alloy 660 Overall   |
| <b>Material:</b>                                      | Plastic Polyamide Locking Feature  |
| <b>Material Document And Classification:</b>          | Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall |
| <b>Surface Treatment:</b>                             | Passivate Overall  |
| <b>Surface Treatment Document And Classification:</b> | Ams 2700, Method 1, Ty2 Or Ty8, Cl1 Assn Std Single Treatment Response Overall   |
| <b>Thread Series Designator:</b>                      | Unjf   |

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6304PU4H> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.