

## P/N NAS6304U11D

### **Description**

Fastener Length: 1-1/16", Thread: 1/4-28, Thread Length: 25/64

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS6304U11D

Minimum Qty (MOQ):

NSN: 5306-00-357-2075

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 013280, Alum Bolts









<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS6304U11D Specifications

| Thread Class:  | 3a   |
|--|--|
| Thread Direction:  | Right-hand   |
| Thread Length:   | 0.345 Inches Minimum And 0.395 Inches Maximum  |
| Fastener Length:   | 1.043 Inches Minimum And 1.073 Inches Maximum  |
| Head Style:  | Dished Hexagon   |
| Head Height:   | 0.125 Inches Minimum And 0.140 Inches Maximum  |
| Width Between Flats:   | 0.430 Inches Minimum And 0.439 Inches Maximum  |
| Grip Diameter:   | 0.2490 Inches Minimum And 0.2495 Inches Maximum  |
| Shank Unthreaded Hole Diameter:                                  | 0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole                                      |
| Nominal Thread Diameter:   | 0.250 Inches   |
| Grip Length:   | 0.678 Inches Minimum And 0.698 Inches Maximum  |
| Thread Quantity Per Inch:  | 28   |
| Minimum Tensile Strength:  | 160000 Pounds Per Square Inch  |
| Distance From Head Largest Bearing Surface To Shank Hole Center: | 0.913 Inches Minimum First Hole And 0.963 Inches Maximum First Hole                                      |
| Surface Finish:  | 32.0 Microinches Bearing Surface Of Head   |
| Surface Finish:  | 32.0 Microinches Grip  |
| Surface Finish:  | 32.0 Microinches Threads   |
| Material:  | Iron Alloy 660 Overall   |
| Material Document And Classification:                            | Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall |
| Surface Treatment:   | Passivate Overall  |
| Surface Treatment Document And Classification:                   | Nas 4003 Assn Std Single Treatment Response Overall  |
| Thread Series Designator:  | Unjf   |
| Specification/standard Data:                                     | 80205-nas 6304 Professional/industrial Association Standard  |
|  |  |

## **How to Order**

Order this shear bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/shear+bolts/NAS6304U11D">https://military-fasteners.com/bolts/shear+bolts/NAS6304U11D</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.