

Description

Fastener Length: 1-1/4", Thread: 1/4-28, Thread Length: 25/64

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6304U14D
Minimum Qty (MOQ):	5
NSN:	5306-00-500-1944
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	013280, Alum Bolts



\* See page 2 for technical characteristics

## P/N NAS6304U14D Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.345 Inches Minimum And 0.395 Inches Maximum
<b>Fastener Length:</b>	1.230 Inches Minimum And 1.260 Inches Maximum
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.125 Inches Minimum And 0.140 Inches Maximum
<b>Width Between Flats:</b>	0.430 Inches Minimum And 0.439 Inches Maximum
<b>Grip Diameter:</b>	0.2490 Inches Minimum And 0.2495 Inches Maximum
<b>Shank Unthreaded Hole Diameter:</b>	0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Grip Length:</b>	0.865 Inches Minimum And 0.885 Inches Maximum
<b>Thread Quantity Per Inch:</b>	28
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b>	1.050 Inches Minimum First Hole And 1.100 Inches Maximum First Hole
<b>Surface Finish:</b>	32.0 Microinches Bearing Surface Of Head
<b>Surface Finish:</b>	32.0 Microinches Grip
<b>Surface Finish:</b>	32.0 Microinches Threads
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas6304 Professional/Industrial Association Standard

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6304U14D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.