

**Description**

Fastener Length: ", Thread: 1/4-28, Thread Length: "

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS6304U2D
Minimum Qty (MOQ):	10 EA
NSN:	5306-01-479-1417
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N NAS6304U2D Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.370 Inches Nominal
<b>Fastener Length:</b>	0.495 Inches Nominal
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.249 Inches Nominal
<b>Width Between Flats:</b>	0.429 Inches Minimum And 0.439 Inches Maximum
<b>Grip Diameter:</b>	0.249 Inches Nominal
<b>Shank Unthreaded Hole Diameter:</b>	0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Grip Length:</b>	0.125 Inches Nominal
<b>Thread Quantity Per Inch:</b>	28
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b>	0.170 Inches Nominal First Hole
<b>Material:</b>	Steel Corrosion Resisting Overall
<b>Material Document And Classification:</b>	Ams5731 Assn Std 1st Material Response Overall Or Ams5732 Assn Std 2nd Material Response Overall Or Ams5737 Assn Std 3rd Material Response Overall
<b>Surface Treatment:</b>	Phosphate Overall
<b>Surface Treatment Document And Classification:</b>	Nas4003 Assn Std Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6304U2D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.