

Description

Fastener Length: 2-", Thread: 1/4-28, Thread Length: "

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6304U32
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-498-6706
Schedule B:	7318.15.8085
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N NAS6304U32 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.370 Inches Nominal
Fastener Length:	2.370 Inches Nominal
Head Style:	Dished Hexagon
Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Width Between Flats:	0.429 Inches Minimum And 0.439 Inches Maximum
Grip Diameter:	2.490 Inches Minimum And 2.500 Inches Maximum
End Item Identification:	F-22 Raptor
Nominal Thread Diameter:	0.250 Inches
Grip Length:	2.000 Inches Nominal
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Part Name Assigned By Controlling Agency:	Bolt
Material:	Iron Alloy 660 Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6304U32> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.