

P/N NAS6304U32

Description

Fastener Length: 2-", Thread: 1/4-28, Thread Length: "

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

| SKU / Model: | NAS6304U32 |
|--------------------|------------------|
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5306-01-498-6706 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |



^{*} See page 2 for technical characteristics

P/N NAS6304U32 Specifications

| Thread Class: | 3a |
|---|---|
| Thread Direction: | Right-hand |
| Thread Length: | 0.370 Inches Nominal |
| Fastener Length: | 2.370 Inches Nominal |
| Head Style: | Dished Hexagon |
| Head Height: | 0.125 Inches Minimum And 0.140 Inches Maximum |
| Width Between Flats: | 0.429 Inches Minimum And 0.439 Inches Maximum |
| Grip Diameter: | 2.490 Inches Minimum And 2.500 Inches Maximum |
| End Item Identification: | F-22 Raptor |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 2.000 Inches Nominal |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Part Name Assigned By Controlling Agency: | Bolt |
| Material: | Iron Alloy 660 Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/NAS6304U32 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.