

Description

Fastener Length: 3-1/8", Thread: 1/4-28, Thread Length: "

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6304U45D
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-410-8547
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS6304U45D Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.370 Inches Nominal
Fastener Length:	3.183 Inches Nominal
Head Style:	Hexagon
Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Width Between Flats:	0.2490 Inches Minimum And 0.2495 Inches Maximum
Grip Diameter:	0.2490 Inches Minimum And 0.2495 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	2.813 Inches Nominal
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6304U45D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.