

P/N NAS6304U4H

Description

Fastener Length: 5/8", Hole Diameter: 3/64", Thread: 1/4-28, Thread Length: 25/64

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS6304U4H

Minimum Qty (MOQ): 5

NSN: 5306-00-500-1470

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N NAS6304U4H Specifications

3a
Right-hand
0.345 Inches Minimum And 0.395 Inches Maximum
0.605 Inches Minimum And 0.635 Inches Maximum
Dished Hexagon
0.125 Inches Minimum And 0.140 Inches Maximum
0.430 Inches Minimum And 0.439 Inches Maximum
0.051 Inches Nominal
0.2490 Inches Minimum And 0.2495 Inches Maximum
0.250 Inches
0.240 Inches Minimum And 0.260 Inches Maximum
3
Drilled
28
160000 Pounds Per Square Inch
Hexagon Corners
32.0 Microinches Bearing Surface Of Head
32.0 Microinches Grip
32.0 Microinches Threads
Iron Alloy 660 Overall
Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Unjf
80205-nas6304 Professional/industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/NAS6304U4H and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.