

**Description**

Fastener Length: 15/16", Hole Diameter: 3/64", Thread: 1/4-28, Thread Length: 25/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS6304U9DH                               |
| Minimum Qty (MOQ):      | 5 EA                                      |
| NSN:                    | 5306-01-013-3991                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N NAS6304U9DH Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>  | 3a  |
| <b>Thread Direction:</b>  | Right-hand  |
| <b>Thread Length:</b>   | 0.345 Inches Minimum And 0.395 Inches Maximum                       |
| <b>Fastener Length:</b>   | 0.917 Inches Minimum And 0.947 Inches Maximum                       |
| <b>Head Style:</b>  | Dished Hexagon  |
| <b>Head Height:</b>   | 0.125 Inches Minimum And 0.140 Inches Maximum                       |
| <b>Width Between Flats:</b>   | 0.430 Inches Minimum And 0.439 Inches Maximum                       |
| <b>Hole Diameter:</b>   | 0.051 Inches Nominal  |
| <b>Grip Diameter:</b>   | 0.2490 Inches Minimum And 0.2495 Inches Maximum                     |
| <b>Shank Unthreaded Hole Diameter:</b>                                  | 0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole |
| <b>Nominal Thread Diameter:</b>   | 0.250 Inches  |
| <b>Grip Length:</b>   | 0.552 Inches Minimum And 0.572 Inches Maximum                       |
| <b>Hole Quantity:</b>   | 3   |
| <b>Hole Type:</b>   | Drilled   |
| <b>Thread Quantity Per Inch:</b>  | 28  |
| <b>Minimum Tensile Strength:</b>  | 160000 Pounds Per Square Inch                                       |
| <b>Hole Configuration Style:</b>  | Hexagon Corners   |
| <b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b> | 0.737 Inches Minimum First Hole And 0.787 Inches Maximum First Hole |
| <b>Material:</b>  | Iron Alloy 660 Overall  |
| <b>Surface Treatment:</b>   | Passivate Overall   |
| <b>Thread Series Designator:</b>  | Unjf  |
| <b>Specification/standard Data:</b>                                     | 80205-nas6304 Professional/Industrial Association Standard          |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6304U9DH> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.