

P/N NAS6305-13D

Description

Fastener Length: 1-1/4", Thread: 1/4-24, Thread Length: 29/64",

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS630513D

Minimum Qty (MOQ):

NSN: 5306-01-347-9781

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)







P/N NAS6305-13D Specifications

3a
Right-hand
0.413 Inches Minimum And 0.463 Inches Maximum
1.235 Inches Minimum And 1.265 Inches Maximum
Dished Hexagon
0.156 Inches Minimum And 0.171 Inches Maximum
0.492 Inches Minimum And 0.502 Inches Maximum
0.3110 Inches Minimum And 0.3120 Inches Maximum
0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole
0.312 Inches
0.802 Inches Minimum And 0.822 Inches Maximum
24
160000 Pounds Per Square Inch
1.068 Inches Nominal First Hole
32.0 Microinches Bearing Surface Of Head32.0 Microinches Grip32.0 Microinches Threads
Iron Alloy 660 Overall
Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Cadmium Overall And Chromate Overall
Qq-p-416 Ty2 Fed Spec Single Treatment Response Overall
Unjf
80205-nas6305 Professional/industrial Association Standard

How to Order

Order this machine bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/NAS6305-13D and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.