

P/N NAS6305-21D

Military-Fasteners.com

Description

Fastener Length: 1-3/4", Thread: 1/4-24, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NAS630521D
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-421-6151
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS6305-21D Specifications

Thread Length:0.438 Inches NominalFastener Length:1.735 Inches Minimum And 1.765 Inches MaximumHead Style:Dished HexagonHead Style:0.156 Inches Minimum And 0.171 Inches MaximumWidth Between Flats:0.492 Inches Minimum And 0.502 Inches MaximumGrip Diameter:0.3110 Inches Minimum And 0.3120 Inches MaximumShank Unthreaded Hole Diameter:0.3120 Inches Minimum And 0.3120 Inches Maximum First HoleNominal Thread Diameter:0.312 InchesMinimum And 1.322 Inches MaximumShank Unthreaded Hole Diameter:0.312 Inches0.312 InchesGrip Length:1.302 Inches Minimum And 1.322 Inches MaximumFeatures Provided:1.302 Inches Minimum And 1.322 Inches MaximumThread Quantity Per Inch:24Minimum Tensile Strength:160000 Pounds Per Square InchDistance From Head Largest Bearing Surface To Shank Hole Center:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Inch Allog 660 OverallMaterial Document And Classification:Cambin Overall And Chromate OverallSurface Treatment:Cambin Overall And Chromate Overall	Thread Class:	3a
Fastener Length:1.735 Inches Minimum And 1.765 Inches MaximumHead Style:Dished HexagonHead Height:0.156 Inches Minimum And 0.171 Inches MaximumWidth Between Flats:0.492 Inches Minimum And 0.502 Inches MaximumGrip Diameter:0.3110 Inches Minimum And 0.3120 Inches MaximumShank Unthreaded Hole Diameter:0.3120 Inches Minimum And 0.3120 Inches Maximum First HoleNominal Thread Diameter:0.312 Inches Minimum And 0.3120 Inches Maximum First HoleNominal Thread Diameter:0.302 Inches Minimum And 1.322 Inches Maximum First HoleFeatures Provided:1.302 Inches Minimum And 1.322 Inches Maximum First HoleThread Quantity Per Inch:24Minimum Tensile Strength:1.6000 Pounds Per Square InchDistance From Head Largest Bearing Surface To Shank Hole2.558 Inches Minimum First Hole And 1.578 Inches Maximum First HoleSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripMaterial Document And Classification:ms5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material ResponseSurface Treatment:Cardimu Overall And Chromate OverallSurface Treatment:Cardimu Overall And Chromate OverallSurface Treatment Document And Classification:0.49-416 Ty2 Cl2 Fed Spec Single Treatment Response Overall <th>Thread Direction:</th> <th>Right-hand</th>	Thread Direction:	Right-hand
Head Style:Dished HexagonHead Height:0.156 Inches Minimum And 0.171 Inches MaximumWidth Between Flats:0.492 Inches Minimum And 0.502 Inches MaximumGrip Diameter:0.3110 Inches Minimum And 0.3120 Inches Maximum First HoleShak Unthreaded Hole Diameter:0.076 Inches Minimum And 0.3120 Inches Maximum First HoleNominal Thread Diameter:0.076 Inches Minimum And 0.3120 Inches Maximum First HoleNominal Thread Diameter:0.312 InchesGrip Length:1.302 Inches Minimum And 1.322 Inches MaximumFeatures Provided:Finished HeadThread Quantity Per Inch:4Minimum Tensile Strength:1.60000 Pounds Per Square InchDistance From Head Largest Bearing Surface To Shank Hole Center:3.158 Inches Minimum First Hole And 1.578 Inches Maximum First HoleSurface Finish:3.2.0 Microinches Bearing Surface Of HeadSurface Finish:3.2.0 Microinches GripSurface Finish:3.2.0 Microinches GripSurface Finish:3.2.0 Microinches Strengt Surface Of HeadMaterial:Iron Alloy 660 OverallMaterial:Iron Alloy 660 OverallSurface Treatment:Camium Overall And Chromate Overall Or Ams5737 Assn Std Single Material Response OverallSurface Treatment:Gamium Overall And Chromate OverallSurface Treatment Document And Classification:Min Overall And Chromate OverallThread Series Designator:Unjf	Thread Length:	0.438 Inches Nominal
Head Height:0.156 Inches Minimum And 0.171 Inches MaximumWidth Between Flats:0.492 Inches Minimum And 0.502 Inches MaximumGrip Diameter:0.3110 Inches Minimum And 0.3120 Inches Maximum First HoleShank Unthreaded Hole Diameter:0.076 Inches Minimum First Hole And 0.086 Inches Maximum First HoleNominal Thread Diameter:0.312 InchesGrip Length:1.302 Inches Minimum And 1.322 Inches Maximum First HoleFeatures Provided:Finished HeadThread Quantity Per Inch:24Minimum Tensile Strength:160000 Pounds Per Square InchDistance From Head Largest Bearing Surface To Shank Hole Center:32.0 Microinches Braing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches StrengtsSurface Finish:32.0 Microinches StrengtsSurface Finish:32.0 Microinches StrengtsSurface Finish:32.0 Microinches StrengtsSurface Finish:32.0 Microinches ThreadsSurface Finish:32.0 Microinches ThreadsSurface Freatment:Coadmium Overall And Chromate OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment:OcerallSurface Treatment Document And Classification:0q-p416 Ty2 Cl2 Fed Spec Single Treatment Response OverallSurface Treatment Document And Classification:0q-p416 Ty2 Cl2 Fed Spec Single Treatment Response OverallSurface Treatment Document And Classification:0q-p416 Ty2 Cl2 Fed Spec	Fastener Length:	1.735 Inches Minimum And 1.765 Inches Maximum
Width Between Flats:0.492 Inches Minimum And 0.502 Inches MaximumGrip Diameter:0.3110 Inches Minimum And 0.3120 Inches Maximum First HoleShank Unthreaded Hole Diameter:0.076 Inches Minimum First Hole And 0.086 Inches Maximum First HoleNominal Thread Diameter:0.312 InchesGrip Length:1.302 Inches Minimum And 1.322 Inches MaximumFeatures Provided:Finished HeadThread Quantity Per Inch:24Minimum Tensile Strength:160000 Pounds Per Square InchDistance From Head Largest Bearing Surface To Shank Hole3.558 Inches Minimum First Hole And 1.578 Inches Maximum First HoleSurface Finish:3.2.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial Document And Classification:Miss731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material ResponseSurface Treatment:Cadmium Overall And Chromate OverallFued Series Designator:Unjf	Head Style:	Dished Hexagon
Grip Diameter:0.3110 Inches Minimum And 0.3120 Inches MaximumShank Unthreaded Hole Diameter:0.076 Inches Minimum First Hole And 0.086 Inches Maximum First HoleNominal Thread Diameter:0.312 InchesGrip Length:1.302 Inches Minimum And 1.322 Inches MaximumFeatures Provided:Finished HeadThread Quantity Per Inch:24Minimum Tensile Strength:16000 Pounds Per Square InchDistance From Head Largest Bearing Surface To Shank Hole center:1.558 Inches Minimum First Hole And 1.578 Inches Maximum First HoleSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:Surfolo GoverallMaterial:Iron Allo 660 OverallMaterial Document And Classification:Cadmium Overall And Chromate Overall Or Ams5737 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment:Oq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response OverallThread Series Designator:Unjf	Head Height:	0.156 Inches Minimum And 0.171 Inches Maximum
Shark Unthreadel Hole Diameter:0.076 Inches Minimum First Hole And 0.086 Inches Maximum First HoleNominal Thread Diameter:0.312 InchesGrip Length:1.302 Inches Minimum And 1.322 Inches MaximumFeatures Provided:Fnished HeadThread Quantity Per Inch:24Minimum Tensile Strength:160000 Pounds Per Square InchDistance From Head Largest Bearing Surface To Shank Hole Center:3.558 Inches Minimum First Hole And 1.578 Inches Maximum First HoleSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial Document And Classification:Condmiu OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:0q-p-416 Ty2 Cl2 Fed Spec Single Treatment Response OverallThread Series Designator:Unif	Width Between Flats:	0.492 Inches Minimum And 0.502 Inches Maximum
Nominal Thread Diameter:0.312 InchesGrip Length:1.302 Inches Minimum And 1.322 Inches MaximumFeatures Provided:Finished HeadThread Quantity Per Inch:24Minimum Tensile Strength:160000 Pounds Per Square InchDistance From Head Largest Bearing Surface To Shank Hole Center:2.558 Inches Minimum First Hole And 1.578 Inches Maximum First HoleSurface Finish:2.0.0 Microinches Bearing Surface Of HeadSurface Finish:2.0.0 Microinches GripSurface Finish:2.0.0 Microinches GripMaterialIron Alloy 660 OverallMaterial Document And Classification:Cadimum Overall And Chromate OverallSurface Treatment Document And Classification:0q-p-416 Ty2 Cl2 Fed Spec Single Treatment Response OverallThread Series Designator:Unif	Grip Diameter:	0.3110 Inches Minimum And 0.3120 Inches Maximum
Grip Length:1.302 Inches Minimu And 1.322 Inches MaximumFeatures Provided:I.302 Inches Minimu And 1.322 Inches MaximumFeatures Provided:Finished HeadThread Quantity Per Inch:24Minimum Tensile Strength:160000 Pounds Per Square InchDistance From Head Largest Bearing Surface To Shank Hole Center:1.558 Inches Minimum First Hole And 1.578 Inches Maximum First HoleSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallMaread Series Designator:Unjf	Shank Unthreaded Hole Diameter:	0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole
Features Provided:Finished HeadFeatures Provided:Finished HeadThread Quantity Per Inch:24Minimum Tensile Strength:16000 Pounds Per Square InchDistance From Head Largest Bearing Surface To Shank Hole Center:1.558 Inches Minimum First Hole And 1.578 Inches Maximum First HoleSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Cadmium Overall And Chromate OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:0q-p-416 Ty2 Cl2 Fed Spec Single Treatment Response OverallThread Series Designator:Unjf	Nominal Thread Diameter:	0.312 Inches
Thread Quantity Per Inch:24Minimum Tensile Strength:16000 Pounds Per Square InchDistance From Head Largest Bearing Surface To Shank Hole center:1.558 Inches Minimum First Hole And 1.578 Inches Maximum First HoleSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Cadmium Overall And Chromate OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Material Single Material Response OverallThread Series Designator:Unjf	Grip Length:	1.302 Inches Minimum And 1.322 Inches Maximum
Minimum Tensile Strength:160000 Pounds Per Square InchDistance From Head Largest Bearing Surface To Shank Hole Center:1.558 Inches Minimum First Hole And 1.578 Inches Maximum First HoleSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response OverallThread Series Designator:Unjf	Features Provided:	Finished Head
Distance From Head Largest Bearing Surface To Shank Hole Center:1.558 Inches Minimum First Hole And 1.578 Inches Maximum First HoleSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Cadmium Overall And Chromate OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Oq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response OverallThread Series Designator:Unjf	Thread Quantity Per Inch:	24
Center:1.558 Inches Minimum First Hole And 1.578 Inches Maximum First HoleSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material ResponseSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Oq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response OverallUnjfUnjf	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Surface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:32.0 Microinches ThreadsMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response OverallInjfUnjf		1.558 Inches Minimum First Hole And 1.578 Inches Maximum First Hole
Surface Finish:32.0 Microinches ThreadsMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response OverallThread Series Designator:Unjf	Surface Finish:	32.0 Microinches Bearing Surface Of Head
Material:Iron Alloy 660 OverallMaterial Document And Classification:Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response OverallThread Series Designator:Unjf	Surface Finish:	32.0 Microinches Grip
Material Document And Classification:Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response OverallThread Series Designator:Unjf	Surface Finish:	32.0 Microinches Threads
Material Document And Classification: Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response Overall Thread Series Designator: Unjf	Material:	Iron Alloy 660 Overall
Surface Treatment Document And Classification: Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response Overall Thread Series Designator: Unjf	Material Document And Classification:	
Thread Series Designator: Unjf	Surface Treatment:	Cadmium Overall And Chromate Overall
	Surface Treatment Document And Classification:	Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response Overall
Specification/standard Data: 80205-nas6305 Professional/industrial Association Standard	Thread Series Designator:	Unjf
	Specification/standard Data:	80205-nas6305 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/machine+bolts/NAS6305-21D</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.