

Description

Fastener Length: 1-53/64", Thread: 5/16-24, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS630522D
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-398-0302
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS6305-22D Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.438 Inches Nominal
Fastener Length:	1.798 Inches Minimum And 1.828 Inches Maximum
Head Style:	Hexagon
Head Height:	0.156 Inches Minimum And 0.171 Inches Maximum
Width Between Flats:	0.492 Inches Minimum And 0.502 Inches Maximum
Grip Diameter:	0.3115 Inches Minimum And 0.3120 Inches Maximum
Shank Unthreaded Hole Diameter:	0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole
Nominal Thread Diameter:	0.3125 Inches
Grip Length:	1.365 Inches Minimum And 1.385 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Distance From Head Largest Bearing Surface To Shank Hole Center:	1.606 Inches Minimum First Hole And 1.656 Inches Maximum First Hole
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Color:	Green Threads
Material:	Iron Alloy 660 Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty I, CI 1 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6305 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS6305-22D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.