

P/N NAS6305L2

Military-Fasteners.com

Description

Fastener Length: 37/64", Thread: 1/4-24, Thread Length: 29/64"

* Manufacturer certifications are shipped with your order $\underline{\mathsf{FREE}}$ of charge

Order this part online

Additional Information

| SKU / Model: | NAS6305L2 |
|-------------------------|---------------------------------------|
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5306-01-297-7529 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |
| National Motor Freight: | 156600, Plastic / Rubber Article Viz: |



P/N NAS6305L2 Specifications

| Thread Class: | За |
|--|--|
| Thread Direction: | Right-hand |
| Thread Length: | 0.413 Inches Minimum And 0.463 Inches Maximum |
| Fastener Length: | 0.548 Inches Minimum And 0.578 Inches Maximum |
| Head Style: | Dished Hexagon |
| Head Height: | 0.156 Inches Minimum And 0.171 Inches Maximum |
| Width Between Flats: | 0.492 Inches Minimum And 0.502 Inches Maximum |
| Locking Feature: | Patch Threads Or Pellet Threads Or Strip Threads |
| Grip Diameter: | 0.3110 Inches Minimum And 0.3120 Inches Maximum |
| Nominal Thread Diameter: | 0.312 Inches |
| Grip Length: | 0.115 Inches Minimum And 0.135 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Surface Finish: | 32.0 Microinches Bearing Surface Of Head |
| Surface Finish: | 32.0 Microinches Grip |
| Surface Finish: | 32.0 Microinches Threads |
| Material: | Iron Alloy 660 Fastener |
| Material: | Plastic Polyamide Locking Feature |
| Material Document And Classification: | Ams 5731 Assn Std Single Material Response Fastener Or Ams 5737 Assn Std Single Material Response Fastener |
| Surface Treatment: | Cadmium Fastener And Chromate Fastener |
| Surface Treatment Document And Classification: | Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Fastener |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas6305 Professional/industrial Association Standard |
| | |

How to Order

Order this (d-lab) bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/shear+bolts/NAS6305L2</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.