



Military-Fasteners.com

P/N NAS6305L6

Description

Fastener Length: 1-1/4", Thread: 1/4-24, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6305L6
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-300-3311
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093470, Bolts / Nuts I / S



* See page 2 for technical characteristics

P/N NAS6305L6 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.438 Inches Nominal
Fastener Length:	1.251 Inches Nominal
Head Style:	Dished Hexagon
Head Height:	0.156 Inches Minimum And 0.171 Inches Maximum
Width Between Flats:	0.497 Inches Nominal
Locking Feature:	Detent Ring Threads
Grip Diameter:	0.312 Inches Nominal
Nominal Thread Diameter:	0.312 Inches
Grip Length:	0.803 Inches Minimum And 0.823 Inches Maximum
Thread Quantity Per Inch:	24
Special Features:	Locking Element Is Plastic Per Mil-f-18240 And Qpl18240;bolt Marked With Green Dye Or Paint On The Thread End
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6305L6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.