

**Description**

Fastener Length: 1-1/4", Thread: 1/4-24, Thread Length: 7/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS6305L6
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-300-3311
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093470, Bolts / Nuts I / S

NO IMAGE  
AVAILABLE

## P/N NAS6305L6 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.438 Inches Nominal
<b>Fastener Length:</b>	1.251 Inches Nominal
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.156 Inches Minimum And 0.171 Inches Maximum
<b>Width Between Flats:</b>	0.497 Inches Nominal
<b>Locking Feature:</b>	Detent Ring Threads
<b>Grip Diameter:</b>	0.312 Inches Nominal
<b>Nominal Thread Diameter:</b>	0.312 Inches
<b>Grip Length:</b>	0.803 Inches Minimum And 0.823 Inches Maximum
<b>Thread Quantity Per Inch:</b>	24
<b>Special Features:</b>	Locking Element Is Plastic Per Mil-f-18240 And Qpl18240;bolt Marked With Green Dye Or Paint On The Thread End
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6305L6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.