

**Description**

Fastener Length: 1-5/64", Thread: 1/4-24, Thread Length: 7/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS6305U10Y
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-435-1735
Schedule B:	7318.15.2091
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N NAS6305U10Y Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.438 Inches Nominal
<b>Fastener Length:</b>	1.048 Inches Minimum And 1.078 Inches Maximum
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.156 Inches Minimum And 0.171 Inches Maximum
<b>Width Between Flats:</b>	0.492 Inches Minimum And 0.502 Inches Maximum
<b>Shoulder Diameter:</b>	0.342 Inches Minimum All Shoulders And 0.343 Inches Maximum All Shoulders
<b>Shoulder Length:</b>	0.615 Inches Minimum All Shoulders And 0.635 Inches Maximum All Shoulders
<b>Nominal Thread Diameter:</b>	0.312 Inches
<b>Features Provided:</b>	Finished Head
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Minimum Yield Strength:</b>	95000 Pounds Per Square Inch
<b>Shoulder Shape:</b>	Round All Shoulders
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas6305 Professional/industrial Association Standard

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6305U10Y> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.