

P/N NAS6305U13

Description

Fastener Length: 1-1/4", Thread: 1/4-24, Thread Length: 7/16

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS6305U13

Minimum Qty (MOQ):

NSN: 5306-01-498-6716

Schedule B: 7318.15.8085

ECCN: EAR99









P/N NAS6305U13 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.438 Inches Nominal
Fastener Length:	1.235 Inches Minimum And 1.265 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.156 Inches Minimum And 0.171 Inches Maximum
Width Between Flats:	0.492 Inches Minimum And 0.502 Inches Maximum
Grip Diameter:	0.311 Inches Minimum And 0.312 Inches Maximum
End Item Identification:	F/a-22 Raptor
Nominal Thread Diameter:	0.312 Inches
Grip Length:	0.802 Inches Minimum And 0.822 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Part Name Assigned By Controlling Agency:	Bolt
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5731 National Std/spec 1st Material Response Overall Or Ams 5732 National Std/spec 2nd Material Response Overall Or Ams 5737 National Std/spec 3rd Material Response Overall Or Ams 5853 National Std/spec 4th Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Nas 4003 National Std/spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205 - Nas 6305 National Std/spec

How to Order

Order this shear bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/NAS6305U13 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.