

P/N NAS6305U20D

Description

Fastener Length: 1-45/64", Thread: 1/4-24, Thread Length: 1-45/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS6305U20D

Minimum Qty (MOQ): 5

NSN: 5306-01-369-4803

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N NAS6305U20D Specifications

| Thread Class: | 3a |
|--|--|
| Thread Direction: | Right-hand |
| | - |
| Thread Length: | 1.673 Inches Minimum And 1.703 Inches Maximum |
| Fastener Length: | 1.673 Inches Minimum And 1.703 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.156 Inches Minimum And 0.171 Inches Maximum |
| Width Between Flats: | 0.492 Inches Minimum And 0.502 Inches Maximum |
| Grip Diameter: | 0.3115 Inches Minimum And 0.3120 Inches Maximum |
| Shank Unthreaded Hole Diameter: | 0.076 Inches Nominal Grip |
| Nominal Thread Diameter: | 0.312 Inches |
| Grip Length: | 1.240 Inches Minimum And 1.260 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Distance From Head Largest Bearing Surface To Shank Hole Center: | 1.496 Inches Minimum Grip And 1.516 Inches Maximum Grip |
| Surface Finish: | 32.0 Microinches Bearing Surface Of Head |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams 5731 Assn Std 1st Material Response Overall And Ams 5737 Assn Std All Material Responses Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Nas 4003 Assn Std 1st Treatment Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas6305 Professional/industrial Association Standard |
| | |

How to Order

Order this shear bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/NAS6305U20D and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.