

P/N NAS6305U20D

Description

Fastener Length: 1-45/64", Thread: 1/4-24, Thread Length: 1-45/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS6305U20D

Minimum Qty (MOQ): 5

NSN: 5306-01-369-4803

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N NAS6305U20D Specifications

Thread Class:	3a
Thread Direction:	Right-hand
	-
Thread Length:	1.673 Inches Minimum And 1.703 Inches Maximum
Fastener Length:	1.673 Inches Minimum And 1.703 Inches Maximum
Head Style:	Hexagon
Head Height:	0.156 Inches Minimum And 0.171 Inches Maximum
Width Between Flats:	0.492 Inches Minimum And 0.502 Inches Maximum
Grip Diameter:	0.3115 Inches Minimum And 0.3120 Inches Maximum
Shank Unthreaded Hole Diameter:	0.076 Inches Nominal Grip
Nominal Thread Diameter:	0.312 Inches
Grip Length:	1.240 Inches Minimum And 1.260 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Distance From Head Largest Bearing Surface To Shank Hole Center:	1.496 Inches Minimum Grip And 1.516 Inches Maximum Grip
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5731 Assn Std 1st Material Response Overall And Ams 5737 Assn Std All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Nas 4003 Assn Std 1st Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6305 Professional/industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/NAS6305U20D and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.