

**Description**

Thread: 1/4-24, Thread Length: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS6305U30D
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-541-9035
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

# P/N NAS6305U30D Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.413 Inches Minimum And 0.463 Inches Maximum
<b>Fastener Length:</b>	2.298 Inches Minimum And 2.328 Inches Maximum
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.156 Inches Minimum And 0.171 Inches Maximum
<b>Width Between Flats:</b>	0.492 Inches Minimum And 0.502 Inches Maximum
<b>Grip Diameter:</b>	0.3115 Inches Minimum And 0.3120 Inches Maximum
<b>Shank Unthreaded Hole Diameter:</b>	0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole
<b>Shank Unthreaded Hole Diameter:</b>	0.076 Inches Minimum And 0.086 Inches Maximum First Hole
<b>Nominal Thread Diameter:</b>	0.312 Inches
<b>Grip Length:</b>	1.865 Inches Minimum And 1.885 Inches Maximum
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b>	2.106 Inches Minimum First Hole And 2.156 Inches Maximum First Hole
<b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b>	2.106 Inches Minimum And 2.156 Inches Maximum First Hole
<b>Surface Finish:</b>	32.0 Microinches Bearing Surface Of Head
<b>Surface Finish:</b>	32.0 Microinches Grip
<b>Surface Finish:</b>	32.0 Microinches Threads
<b>iii Part Name Assigned By Controlling Agency:</b>	Navy Special Project
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams5731 Assn Std Single Material Response Overall
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas6305 Professional/Industrial Association Standard

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6305U30D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.