

**Description**

Fastener Length: 3-3/16", Hole Diameter: 3/64", Thread: 1/4-24, Thread Length: 29/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS6305U44H                               |
| Minimum Qty (MOQ):      | 1 EA                                      |
| NSN:                    | 5306-01-554-1609                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N NAS6305U44H Specifications

|  |   |
|--|---|
| <b>Thread Class:</b>                             | 3a  |
| <b>Thread Direction:</b>                         | Right-hand                                      |
| <b>Thread Length:</b>                            | 0.413 Inches Minimum And 0.463 Inches Maximum   |
| <b>Fastener Length:</b>                          | 3.188 Inches Nominal                            |
| <b>Head Style:</b>                               | Dished Hexagon                                  |
| <b>Head Height:</b>                              | 0.156 Inches Minimum And 0.171 Inches Maximum   |
| <b>Width Between Flats:</b>                      | 0.492 Inches Minimum And 0.502 Inches Maximum   |
| <b>Hole Diameter:</b>                            | 0.046 Inches Minimum And 0.056 Inches Maximum   |
| <b>Grip Diameter:</b>                            | 0.3115 Inches Minimum And 0.3120 Inches Maximum |
| <b>End Item Identification:</b>                  | C5m   |
| <b>Nominal Thread Diameter:</b>                  | 0.312 Inches                                    |
| <b>Grip Length:</b>                              | 3.438 Inches Minimum                            |
| <b>Hole Quantity:</b>                            | 3   |
| <b>Hole Type:</b>                                | Drilled   |
| <b>Thread Quantity Per Inch:</b>                 | 24  |
| <b>Minimum Tensile Strength:</b>                 | 160000 Pounds Per Square Inch                   |
| <b>Hole Configuration Style:</b>                 | Hexagon Corners                                 |
| <b>Part Name Assigned By Controlling Agency:</b> | Bolt  |
| <b>Material:</b>                                 | Iron Alloy 660 Overall                          |
| <b>Thread Series Designator:</b>                 | Unjf  |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6305U44H> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.