

Description

Fastener Length: 11/16", Thread: 1/4-24, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6305U4D
Minimum Qty (MOQ):	10 EA
NSN:	5306-01-487-2922
Schedule B:	7318.15.8085
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N NAS6305U4D Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.438 Inches Nominal
Fastener Length:	0.688 Inches Nominal
Head Style:	Dished Hexagon
Head Height:	0.156 Inches Minimum And 0.171 Inches Maximum
Width Between Flats:	0.492 Inches Minimum And 0.502 Inches Maximum
Grip Diameter:	0.3115 Inches Minimum And 0.3120 Inches Maximum
Shank Unthreaded Hole Diameter:	0.104 Inches Minimum First Hole And 0.119 Inches Maximum First Hole
Nominal Thread Diameter:	0.312 Inches
Grip Length:	0.250 Inches Nominal
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Distance From Head Largest Bearing Surface To Shank Hole Center:	0.506 Inches Nominal First Hole
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6305U4D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.