

Description

Fastener Length: 5-1/16", Thread: 5/8-18, Thread Length: 7/16",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6305U74
Minimum Qty (MOQ):	5
NSN:	5306-01-536-2560
Schedule B:	7318.15.8085
ECCN:	EAR99



* See page 2 for technical characteristics

P/N NAS6305U74 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.438 Inches Nominal
Fastener Length:	5.063 Inches Nominal
Head Style:	Dished Hexagon
Head Height:	0.163 Inches Nominal
Width Between Flats:	0.497 Inches Nominal
Grip Diameter:	0.3120 Inches Nominal
Nominal Thread Diameter:	0.6250 Inches
Grip Length:	4.625 Inches Nominal
Thread Quantity Per Inch:	18
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Steel Corrosion Resisting Overall
Thread Series Designator:	Unjf

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6305U74> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.