

**Description**

Fastener Length: 61/64", Hole Diameter: 5/64", Thread: 1/4-24, Thread Length: 29/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS6305U8H
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-434-7602
Schedule B:	7318.15.8085
ECCN:	EAR99

NO IMAGE  
AVAILABLE

## P/N NAS6305U8H Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.413 Inches Minimum And 0.463 Inches Maximum
<b>Fastener Length:</b>	0.923 Inches Minimum And 0.953 Inches Maximum
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.156 Inches Minimum And 0.171 Inches Maximum
<b>Width Between Flats:</b>	0.492 Inches Minimum And 0.502 Inches Maximum
<b>Hole Diameter:</b>	0.080 Inches Minimum And 0.090 Inches Maximum
<b>Grip Diameter:</b>	0.3110 Inches Minimum And 0.3120 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.312 Inches
<b>Grip Length:</b>	0.490 Inches Minimum And 0.510 Inches Maximum
<b>Hole Quantity:</b>	3
<b>Hole Type:</b>	Drilled
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Hole Configuration Style:</b>	Hexagon Corners
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6305U8H> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.