



Military-Fasteners.com

P/N NAS6305U9H

Description

Fastener Length: 0-63/64", Hole Diameter: 5/64", Thread: 1/4-24, Thread Length: 29/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6305U9H
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-120-8178
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS6305U9H Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.413 Inches Minimum And 0.463 Inches Maximum
Fastener Length:	0.985 Inches Minimum And 1.015 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.156 Inches Minimum And 0.171 Inches Maximum
Width Between Flats:	0.492 Inches Minimum And 0.502 Inches Maximum
Hole Diameter:	0.070 Inches Minimum And 0.080 Inches Maximum
Grip Diameter:	0.3115 Inches Minimum And 0.3120 Inches Maximum
Nominal Thread Diameter:	0.312 Inches
Grip Length:	0.552 Inches Minimum And 0.572 Inches Maximum
Hole Quantity:	3
Hole Type:	Drilled
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hole Configuration Style:	Hexagon Corners
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6305 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6305U9H> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.