

Description

Fastener Length: 1-7/32", Thread: 3/8-24, Thread Length: 29/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS630612D |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-01-369-3324 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS6306-12D Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.454 Inches Nominal |
| Fastener Length: | 1.189 Inches Minimum And 1.219 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.188 Inches Minimum And 0.203 Inches Maximum |
| Width Between Flats: | 0.554 Inches Minimum And 0.564 Inches Maximum |
| Grip Diameter: | 0.3740 Inches Minimum And 0.3745 Inches Maximum |
| Nominal Thread Diameter: | 0.375 Inches |
| Grip Length: | 0.740 Inches Minimum And 0.760 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Surface Finish: | 32.0 Microinches Bearing Surface Of Head |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams 5731 Assn Std 1st Material Response Overall Or Ams 5737 Assn Std All Material Responses Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Ty 2 Fed Spec 1st Treatment Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas6306 Professional/industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS6306-12D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.