

**Description**

Fastener Length: 1-45/64", Thread: 3/8-24, Thread Length: 29/64", NAS6306 series bolt

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS630620D                                |
| Minimum Qty (MOQ):      | 5   |
| NSN:                    | 5306-01-535-4360                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



## P/N NAS6306-20D Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Thread Length:</b>                                 | 0.454 Inches Nominal  |
| <b>Fastener Length:</b>                               | 1.704 Inches Nominal  |
| <b>Head Style:</b>                                    | Hexagon   |
| <b>Head Height:</b>                                   | 0.188 Inches Minimum And 0.203 Inches Maximum   |
| <b>Width Between Flats:</b>                           | 0.554 Inches Minimum And 0.564 Inches Maximum   |
| <b>Grip Diameter:</b>                                 | 0.3740 Inches Minimum And 0.3745 Inches Maximum   |
| <b>End Item Identification:</b>                       | C-17a Aircraft  |
| <b>Nominal Thread Diameter:</b>                       | 0.375 Inches  |
| <b>Grip Length:</b>                                   | 1.250 Inches Nominal  |
| <b>Thread Quantity Per Inch:</b>                      | 24  |
| <b>Minimum Tensile Strength:</b>                      | 160000 Pounds Per Square Inch   |
| <b>Surface Finish:</b>                                | 32.0 Microinches Bearing Surface Of Head  |
| <b>Part Name Assigned By Controlling Agency:</b>      | Bolt,tension,hex Head,close Tolerance,a286 Cres,short Thread,reduced Major Thread Dia.,nonlocking,160 Ksi Ftu |
| <b>Material:</b>                                      | Iron Alloy 660 Overall  |
| <b>Material Document And Classification:</b>          | Ams 5731 Assn Std 1st Material Response Overall Or Ams 5737 Assn Std All Material Responses Overall           |
| <b>Surface Treatment:</b>                             | Cadmium Overall   |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416 Ty 2 Fed Spec 1st Treatment Response Overall   |
| <b>Thread Series Designator:</b>                      | Unjf  |
| <b>Specification/standard Data:</b>                   | 80205-nas6306 Professional/industrial Association Standard  |

## How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS6306-20D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.