

Description

Fastener Length: 2-23/32", Thread Length: 29/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS630636D
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-523-8321
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N NAS6306-36D Specifications

<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.454 Inches Nominal
<b>Fastener Length:</b>	2.689 Inches Minimum And 2.719 Inches Maximum
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.188 Inches Minimum And 0.203 Inches Maximum
<b>Width Between Flats:</b>	0.552 Inches Minimum And 0.623 Inches Maximum
<b>Grip Diameter:</b>	0.374 Inches Nominal
<b>End Item Identification:</b>	Pre-provisioning Support
<b>Grip Length:</b>	2.240 Inches Minimum And 2.260 Inches Maximum
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Criticality Code Justification:</b>	Mdcl And Agav
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Nas 6303 National Std/spec All Material Responses Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS6306-36D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.