

Description

Fastener Length: 2-23/32", Thread Length: 29/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS630636D
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-523-8321
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS6306-36D Specifications

Thread Direction:	Right-hand
Thread Length:	0.454 Inches Nominal
Fastener Length:	2.689 Inches Minimum And 2.719 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.188 Inches Minimum And 0.203 Inches Maximum
Width Between Flats:	0.552 Inches Minimum And 0.623 Inches Maximum
Grip Diameter:	0.374 Inches Nominal
End Item Identification:	Pre-provisioning Support
Grip Length:	2.240 Inches Minimum And 2.260 Inches Maximum
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Criticality Code Justification:	Mdcl And Agav
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Nas 6303 National Std/spec All Material Responses Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS6306-36D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.