

P/N NAS6306-46D

Description

Fastener Length: 3-11/32", Thread: 3/8-24, Thread Length: 29/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS630646D

Minimum Qty (MOQ): 1 EA

NSN: 5306-01-478-1566

Schedule B: 7318.15.2091

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS6306-46D Specifications

| Thread Class: | 3a |
|--|--|
| Thread Direction: | Right-hand |
| Thread Length: | 0.454 Inches Nominal |
| Fastener Length: | 3.314 Inches Minimum And 3.344 Inches Maximum |
| Head Style: | Dished Hexagon |
| Head Height: | 0.188 Inches Minimum And 0.203 Inches Maximum |
| Width Between Flats: | 0.554 Inches Minimum And 0.564 Inches Maximum |
| Grip Diameter: | 0.374 Inches Nominal |
| End Item Identification: | Fighter Aircraft - First (f18 E/f) |
| Nominal Thread Diameter: | 0.375 Inches |
| Grip Length: | 2.865 Inches Minimum And 2.885 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Criticality Code Justification: | Agav |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams5731 Assn Std 1st Material Response Overall Or Ams5732 Assn Std 2nd Material Response Overall Or Ams5737 Assn Std 3rd Material Response Overall Or Ams5853 Assn Std 4th Material Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/NAS6306-46D and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.