



Military-Fasteners.com

P/N NAS6306-47D

Description

Fastener Length: 3-25/64", Thread: 3/8-24, Thread Length: 29/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS630647D
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-477-9337
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS6306-47D Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.454 Inches Nominal
Fastener Length:	3.391 Inches Nominal
Head Style:	Dished Hexagon
Head Height:	0.188 Inches Minimum And 0.203 Inches Maximum
Width Between Flats:	0.554 Inches Minimum And 0.564 Inches Maximum
Grip Diameter:	0.374 Inches Nominal
Shank Unthreaded Hole Diameter:	0.106 Inches Minimum First Hole And 0.116 Inches Maximum First Hole
Nominal Thread Diameter:	0.375 Inches
Grip Length:	2.937 Inches Nominal
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Distance From Head Largest Bearing Surface To Shank Hole Center:	0.183 Inches Nominal First Hole
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Ams5731 Assn Std 1st Material Response Overall Or Ams5732 Assn Std 2nd Material Response Overall Or Ams5737 Assn Std 3rd Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Nas4003 Assn Std All Treatment Responses Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS6306-47D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.