

Description

Fastener Length: 31/32", Thread: 3/8-24, Thread Length: 29/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6306L8
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-485-5756
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS6306L8 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.454 Inches Nominal
Fastener Length:	0.939 Inches Minimum And 0.969 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.188 Inches Minimum And 0.203 Inches Maximum
Width Between Flats:	0.554 Inches Minimum And 0.564 Inches Maximum
Grip Diameter:	0.373 Inches Minimum And 0.374 Inches Maximum
End Item Identification:	Fighter Aircraft - First (f18 E/f)
Nominal Thread Diameter:	0.375 Inches
Grip Length:	0.490 Inches Minimum And 0.510 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Criticality Code Justification:	Agav
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5731 Assn Std 1st Material Response Overall Or Ams5732 Assn Std 2nd Material Response Overall Or Ams5737 Assn Std 3rd Material Response Overall Or Ams5853 Assn Std 4th Material Response Overall
Surface Treatment Document And Classification:	Qq-p-416, Ty2, Cl2 Fed Spec Single Treatment Response Bearing Surface Of Head
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6306L8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.