

Description

Fastener Length: 31/32", Thread: 3/8-24, Thread Length: 29/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS6306L8 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5306-01-485-5756 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS6306L8 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.454 Inches Nominal |
| Fastener Length: | 0.939 Inches Minimum And 0.969 Inches Maximum |
| Head Style: | Dished Hexagon |
| Head Height: | 0.188 Inches Minimum And 0.203 Inches Maximum |
| Width Between Flats: | 0.554 Inches Minimum And 0.564 Inches Maximum |
| Grip Diameter: | 0.373 Inches Minimum And 0.374 Inches Maximum |
| End Item Identification: | Fighter Aircraft - First (f18 E/f) |
| Nominal Thread Diameter: | 0.375 Inches |
| Grip Length: | 0.490 Inches Minimum And 0.510 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Criticality Code Justification: | Agav |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams5731 Assn Std 1st Material Response Overall Or Ams5732 Assn Std 2nd Material Response Overall Or Ams5737 Assn Std 3rd Material Response Overall Or Ams5853 Assn Std 4th Material Response Overall |
| Surface Treatment Document And Classification: | Qq-p-416, Ty2, Cl2 Fed Spec Single Treatment Response Bearing Surface Of Head |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6306L8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.