

Description

Fastener Length: 1-19/32", Thread: 3/8-24, Thread Length: 29/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6306U18
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-421-5855
Schedule B:	7318.15.8085
ECCN:	EAR99



* See page 2 for technical characteristics

P/N NAS6306U18 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.454 Inches Nominal
Fastener Length:	1.564 Inches Minimum And 1.594 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.188 Inches Minimum And 0.203 Inches Maximum
Width Between Flats:	0.554 Inches Minimum And 0.564 Inches Maximum
Grip Diameter:	0.3740 Inches Minimum And 0.3745 Inches Maximum
End Item Identification:	F-16
Nominal Thread Diameter:	0.375 Inches
Grip Length:	1.115 Inches Minimum And 1.135 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5731 Assn Std 1st Material Response Overall Or Ams 5737 Assn Std 2nd Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6306U18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.