

**Description**

Fastener Length: 1-23/32", Hole Diameter: 1/16", Thread: 3/8-24, Thread Length: 15/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS6306U20DH                              |
| Minimum Qty (MOQ):      | 5 EA                                      |
| NSN:                    | 5306-00-508-6299                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N NAS6306U20DH Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>  | 3a   |
| <b>Thread Direction:</b>  | Right-hand   |
| <b>Thread Length:</b>   | 0.429 Inches Minimum And 0.479 Inches Maximum  |
| <b>Fastener Length:</b>   | 1.689 Inches Minimum And 1.719 Inches Maximum  |
| <b>Head Style:</b>  | Dished Hexagon   |
| <b>Head Height:</b>   | 0.188 Inches Minimum And 0.203 Inches Maximum  |
| <b>Width Between Flats:</b>   | 0.553 Inches Minimum And 0.564 Inches Maximum  |
| <b>Hole Diameter:</b>   | 0.075 Inches Nominal   |
| <b>Grip Diameter:</b>   | 0.3740 Inches Minimum And 0.3750 Inches Maximum  |
| <b>Shank Unthreaded Hole Diameter:</b>                                  | 0.106 Inches Minimum First Hole And 0.116 Inches Maximum First Hole                                      |
| <b>Nominal Thread Diameter:</b>   | 0.375 Inches   |
| <b>Grip Length:</b>   | 1.240 Inches Minimum And 1.260 Inches Maximum  |
| <b>Hole Quantity:</b>   | 3  |
| <b>Hole Type:</b>   | Drilled  |
| <b>Thread Quantity Per Inch:</b>  | 24   |
| <b>Minimum Tensile Strength:</b>  | 160000 Pounds Per Square Inch  |
| <b>Hole Configuration Style:</b>  | Hexagon Corners  |
| <b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b> | 1.496 Inches Minimum First Hole And 1.546 Inches Maximum First Hole                                      |
| <b>Material:</b>  | Iron Alloy 660 Overall   |
| <b>Material Document And Classification:</b>                            | Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall |
| <b>Thread Series Designator:</b>  | Unjf   |
| <b>Specification/standard Data:</b>                                     | 80205-nas6306 Professional/industrial Association Standard   |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6306U20DH> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.