

Description

Fastener Length: 1-27/32", Thread: 3/8-24, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6306U22D
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-345-6686
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS6306U22D Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.444 Inches Nominal
Fastener Length:	1.814 Inches Minimum And 1.844 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.188 Inches Minimum And 0.203 Inches Maximum
Width Between Flats:	0.554 Inches Minimum And 0.564 Inches Maximum
Grip Diameter:	0.3740 Inches Minimum And 0.3745 Inches Maximum
Shank Unthreaded Hole Diameter:	0.070 Inches Minimum First Hole And 0.080 Inches Maximum First Hole
Nominal Thread Diameter:	0.375 Inches
Grip Length:	1.365 Inches Minimum And 1.385 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Distance From Head Largest Bearing Surface To Shank Hole Center:	1.646 Inches Nominal First Hole
Surface Finish:	32.0 Microinches Bearing Surface Of Head32.0 Microinches Grip32.0 Microinches Threads
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6306 Professional/Industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6306U22D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.