

**Description**

Fastener Length: 21/32", Hole Diameter: 1/16", Thread: 3/8-24, Thread Length: 15/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS6306U3                                 |
| Minimum Qty (MOQ):      | 5 EA                                      |
| NSN:                    | 5306-01-063-9905                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N NAS6306U3 Specifications

|                                     |  |
|-------------------------------------|--|
| <b>Thread Class:</b>                | 3a   |
| <b>Thread Direction:</b>            | Right-hand   |
| <b>Thread Length:</b>               | 0.429 Inches Minimum And 0.479 Inches Maximum              |
| <b>Fastener Length:</b>             | 0.627 Inches Minimum And 0.657 Inches Maximum              |
| <b>Head Style:</b>                  | Dished Hexagon   |
| <b>Head Height:</b>                 | 0.188 Inches Minimum And 0.203 Inches Maximum              |
| <b>Width Between Flats:</b>         | 0.554 Inches Minimum And 0.564 Inches Maximum              |
| <b>Hole Diameter:</b>               | 0.075 Inches Nominal                                       |
| <b>Grip Diameter:</b>               | 0.3740 Inches Minimum And 0.3745 Inches Maximum            |
| <b>Nominal Thread Diameter:</b>     | 0.375 Inches   |
| <b>Grip Length:</b>                 | 0.178 Inches Minimum And 0.198 Inches Maximum              |
| <b>Hole Quantity:</b>               | 3  |
| <b>Hole Type:</b>                   | Drilled  |
| <b>Thread Quantity Per Inch:</b>    | 24   |
| <b>Minimum Tensile Strength:</b>    | 160000 Pounds Per Square Inch                              |
| <b>Hole Configuration Style:</b>    | Hexagon Corners  |
| <b>Surface Finish:</b>              | 32.0 Microinches Bearing Surface Of Head                   |
| <b>Surface Finish:</b>              | 32.0 Microinches Grip                                      |
| <b>Surface Finish:</b>              | 32.0 Microinches Threads                                   |
| <b>Material:</b>                    | Iron Alloy 660 Overall                                     |
| <b>Surface Treatment:</b>           | Passivate Overall  |
| <b>Thread Series Designator:</b>    | Unjf   |
| <b>Specification/standard Data:</b> | 80205-nas6306 Professional/industrial Association Standard |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6306U3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.